

42" WIDE PLASMA DISPLAY

SPECIFICATION

Model	P42HHA40US	P42VHA40US	
Screen size	42" wide screen (W 92.2 x H 52.2 cm)	42" wide screen (W 92.1 x H 51.8 cm)	
Aspect ratio	16 : 9		
Weight	31.5 kg		
Outer dimensions	W103.9 x H 64.0 x D 8.7 cm does not include outer projections		
Power supply	110 – 240 V AC 50 / 60Hz		
Current rating	4.2 – 1.8 A	3.2 – 1.35 A	
Number of pixels	1024 (H) x 1024 (V)	852 (H) x 480 (V)	
Colors	1.07 billion		
Corresponding signals	RGB mode	VGA,WVGA,SVGA,XGA,WXGA,SXGA	
	DVI-D mode	VGA,WVGA,SVGA,XGA	
	Comp.video / HDMI mode	480i,576i,480p,576p ,720p,1080i	
	Video mode	NTSC,PAL,SECAM,PAL60,N-PAL,M-PAL,4.43NTSC	
External equipment terminals	VIDEO1 INPUT Video input	RCA terminal 1.0Vp-p/75Ω	
	VIDEO2 INPUT S-video input	S terminal (Y:1.0Vp-p/75Ω、C:0.286Vp-p/75Ω)	
	VIDEO3,4 INPUT Component video input	Y : 1 RCA terminal 1.0Vp-p/75Ω PB/CB : 1 RCA terminal 0.7Vp-p/75Ω PR/CR : 1 RCA terminal 0.7Vp-p/75Ω	
	VIDEO5 INPUT HDMI input	HDMI terminal (HDMI type A Connector)	
	RGB1 input	DVI-D terminal (EIA/CEA-861B Compliant)	
	RGB2 input	mD-sub,3rows,15-pin 0.7Vp-p/75Ω	
	Audio 1,2,3 input	Pin jacks 0.5Vrms (L/R) 3 lines	
	External speaker output	Max. output 10W+10W 6Ω	
	Control terminal	RS-232C D-sub 9-pin	
	Operating conditions	Temperature 0~40°C Humidity 20~80%	
	Regulations	Safety	UL6500,C-UL / EN60065 / IEC60065
EMC		FCC Part 15 Class B, ICES-003 Class B / EN55013 / EN55020 / AS/NZS 1053	
Accessories	User's manuals (3)	Remote control (1)	
	Power cable (1)	AA batteries (2)	

Options:

Wall-mounting Bracket(P-WB4201)/Ceiling unit(P-CT4200)/Desktop stand unit(P-TT4202)

Speaker(P-SP1000: for PDP attachment)

Speaker(P-SP4200)/Speaker stand(P-ST4200)