

50" WIDE PLASMA DISPLAY

SPECIFICATION

Model	P50XHA40WS / P50XHA40US	
Screen size	50" wide screen (W 110.6 x H 62.2 cm)	
Aspect ratio	16 : 9	
Weight	45 kg	
Outer dimensions	W121.6 x H 72.6 x D 10.0 cm does not include outer projections	
Power supply	110 – 240 V AC 50 / 60Hz	
Current rating	4.4 – 1.9 A	
Number of pixels	1366 (H) x 768 (V)	
Colors	1.07 billion	
Corresponding signals	RGB mode	VGA,WVGA,SVGA,XGA,WXGA,SXGA
	DVI-D mode	VGA,WVGA,SVGA,XGA,WXGA
	Comp.video / HDMI mode	480i,576i,480p,576p ,720p,1080i
	Video mode	NTSC,PAL,SECAM,PAL60,N-PAL,M-PAL,4.43NTSC
External equipment terminals	VIDEO1 INPUT	
	Video input	RCA terminal 1.0Vp-p/75Ω
	VIDEO2 INPUT	
	S-video input	S terminal (Y:1.0Vp-p/75Ω、C:0.286Vp-p/75Ω)
	VIDEO3,4 INPUT	Y : 1 RCA terminal 1.0Vp-p/75Ω
	Component video input	PB/CB : 1 RCA terminal 0.7Vp-p/75Ω
		PR/CR : 1 RCA terminal 0.7Vp-p/75Ω
	VIDEO5 INPUT	
	HDMI input (Except P50XHA40WS)	HDMI terminal (HDMI type A Connector)
	RGB1 input	DVI-D terminal (EIA/CEA-861B Compliant)
RGB2 input	mD-sub,3rows,15-pin 0.7Vp-p/75Ω	
Audio 1,2,3 input	Pin jacks 0.5Vrms (L/R) 3 lines	
External speaker output	Max. output 10W+10W 6Ω	
Control terminal	RS-232C D-sub 9-pin	
Operating conditions	Temperature 0~40°C Humidity 20~80%	
Regulations	Safety	UL6500,C-UL / EN60065 / IEC60065
	EMC	FCC Part 15 Class B, ICES-003 Class B / EN55013 / EN55020 / AS/NZS 1053
Accessories	User's manuals (3)	Remote control (1)
	Power cable (1)	AA batteries (2)

Options:

Wall-mounting Bracket(P-WB4201)/Ceiling unit(P-CT4200)/Desktop stand unit(P-TT4202)

Speaker(P-SP1000: for PDP attachment)

Speaker(P-SP5010)/Speaker stand(P-ST5000)