

37" WIDE PANEL DISPLAY**SPECIFICATION**

Model	P37FT05AEB (Product name: P37FT05AEB)	
Screen size	37" wide screen 81.9 cm (W) x 46.1 cm (H)	
Aspect ratio	16 : 9	
Weight	36kg	
Outer dimensions	91.4 (W) x 66.5 (H) x 23.0 (D) cm (does not include outer projections)	
Power supply	110-240 VAC 50/60 Hz	
Current rating	2.0-0.8A	
Number of pixels	1920 (H) x 1080 (V)	
Corresponding signals	RGB mode	VGA,VGA text,WVGA,SVGA,XGA,WXGA,SXGA
	Comp.video mode	SDTV 480i,576i,480P,576P / HDTV 720P,1080i
	Video mode	NTSC,PAL,SECAM,M-PAL,N-PAL,PAL60,4.43NTSC
	TV mode	PAL,SECAM,DVB-T
External equipment terminals	ANTENNA INPUT	TV 75 Ω
	VIDEO1-2 INPUT (SCART input)	SCART terminal
	VIDEO3-4 INPUT (Comp.video)	3 RCA terminals Y: 1 V _{p-p} /75 Ω PB/CB: 0.7 V _{p-p} /75 Ω , PR/CR: 0.7 V _{p-p} /75 Ω
	VIDEO5-6 INPUT (HDMI)	HDMI terminal (HDMI type A connector) SDTV 480i,576i,480P,576P / HDTV 720P,1080i,1080p
	RGB1 INPUT	mD-Sub , 3 rows, 15-pin Picture signal: 0.7 V _{p-p} /75 Ω
	AUDIO1-2 INPUT	2 Pin jacks (L/R) 0.5V _{rms} (2.8V _{rms} /74kΩ (Max.))
	AUDIO OUTPUT ANALOG	2 Pin jacks (L/R) 0.5V _{rms} (2.0V _{rms} /1kΩ (Max.))
	AUDIO OUTPUT DIGITAL	Optical audio terminal
	CONTROL TERMINAL	RS-232C D-sub9 PIN
Speakers	Built-in. (Max. output: 12 W + 12 W, 4 Ω)	
Language (OSD)	English , German , Spanish , French , Italian	
Operating conditions	Temperature 0 to 40°C , Humidity 20 to 80%	
Regulations	Safety	UL60065, C-UL , EN60065 , IEC60065
	EMC	FCC Part 15, ICES-003 (CISPR22) EN55013 (CISPR13) , EN55020 (CISPR20) , EN61000-3-2 , EN61000-3-3 , EN55022 (CISPR22) , EN55024 (CISPR24)
Accessories	1 user' s manual, 1safty precautions, 1 power cable, 4 large ferrite cores, 1 remote control, 2 AA batteries	

Options Swivel unit