

# Specifications



<b>Model Name</b>		<b>LPF-7200</b>	
<b>Liquid Crystal Display Panel</b>		1.3 inches Polysilicon TFT LCD x 3 with micro lens array	
<b>Number of Pixels</b>		1024(H) x 768(V) pixels	
<b>Projection Lens</b>		F-1= 8-2.15 with Lens shift	
<b>Projection Size</b>		36 to 300 Inches	
<b>Lamp</b>		250W NSH Lamp	
<b>Screen Luminance</b>		2800 ANSI Lumens	
<b>Uniformity</b>		over 80%	
<b>Contrast Ratio</b>		over 300:1	
<b>Connectable PC</b>		XGA(real), VGA, SVGA, SXGA(resizing), UXGA(Compression)	
<b>Video System</b>		NTSC, PAL, SECAM, N-PAL, M-PAL, 4.43NTSC	
<b>Input Terminal</b>	Input 1 (Selectable)	Digital RGB	DVI digital 24 pin x 1
		Analog RGB	HD D-sub 15 pin x 1
	Input 2	Analog RGB	HD D-sub 15 pin x 1
	Input 3	RGB/DVD	BNC (5) x 1 (R/Cr/Pr, G/Y, B/Cb/Pb, H, V)
	Video		RCA pin, S-terminal
	Audio		Stereo mini jack x 3 (RGB), RCA(L/R) pin x 1 (Video)
<b>Output Terminal</b>	Analog RGB		HD D-sub 15pin x 1
	Audio		Stereo mini jack x 1
<b>Sound Output</b>		3W + 3W Stereo Speakers	
<b>Remote Control</b>	RS-232C	9 pin D-Sub x 1	
	Mouse	PS/2 Mini DIN 8 pin x 1, USB x 1	
<b>Power Supply</b>		AC100-240V 50/60Hz	
<b>Power Consumption</b>		380W	
<b>Dimensions</b>		150(H) x 282(W) x 429(D) [16.8(H) x 11.0(W) x 5.8(D)]	
<b>Weight</b>		7.8kg(17.2lbs)	
<b>Accessories</b>		Remote Control, Lens Cap, RGB Cable, Users Manual, Mouse Cable(PS/2)	
		Video Cable, Air Filter, Power Cable, Batteries	
<b>Option</b>		Lamp Box, Cable for Wired remote control	

•Specifications and design subject to change without notice for further improvement.

## Projection Distance and Screen Size

Size (Inch)	60	80	100	150	200	250	300
Projection L (m)	2.1	2.9	3.6	5.4	7.3	9.1	10.9
Distance L (Ft)	6.9	9.5	11.8	17.7	24.0	29.9	35.8